


2MM PowerGrip® Pitch Timing Belt Pulleys

For 6MM Belts Type H

Clear Anodized Aluminum Alloy

ALL DIMENSIONS IN INCHES

	Code Number	# of Teeth	Type	Pulley Pitch Diam	Pulley Diam	Hub Diam +/- .015"	Overall Width +/- .010"	Face Width +/- .010"	Belt Width +/- .010"	Hub Width +/- .015"	Setscrew Location +/- .015"	Setscrew Size	Stock Bore Diam + .001 / - .000"
 <p style="text-align: center;">Type H</p>	60-2PG-06M	60	H	1.504	1.484	1.148	.750	.375	.375	.375	.188	8-32**	1/4
	62-2PG-06M	62	H	1.554	1.534	1.148						8-32**	1/4
	68-2PG-06M	68	H	1.704	1.684	1.185						8-32**	1/4
	72-2PG-06M	72	H	1.805	1.785	1.185						8-32**	5/16
	74-2PG-06M	74	H	1.855	1.835	1.215						8-32**	5/16
	80-2PG-06M	80	H	2.005	1.985	1.500						8-32**	5/16
	90-2PG-06M	90	H	2.256	2.236							8-32**	5/16
	100-2PG-06M	100	H	2.506	2.486							8-32**	5/16
	120-2PG-06M	120	H	3.008	2.988							10-32**	3/8

P/N Construction: (Code Number) (Bore Diameter) (Type)(Material Code)

	PULLEY DIAMETER TOLERANCES
	60 - 80 Teeth = +.003 / -.000
	81 - 120 Teeth = +.004 / -.000
	2PG Working Depth = .0295"
	NOTES
	* One (1) setscrew furnished.
	** Two (2) setscrews furnished at 90 degrees.

Ph: (217) 428-9043
 Fx: (877) 1 FAX DSI



Email: info@DSIpulleys.com
 Website: www.DSIpulleys.com