


# 2MM PowerGrip® Pitch Timing Belt Pulleys

## For 9MM Belts      Type H

Clear Anodized Aluminum Alloy

### ALL DIMENSIONS IN INCHES

Code Number	# of Teeth	Type	Pulley Pitch Diam	Pulley Diam	Hub Diam	Overall Width	Face Width	Belt Width	Hub Width	Setscrew Location	Setscrew Size	Stock Bore Diam
					+/- .015"	+/- .010"	+/- .010"	+/- .010"	+/- .015"	+/- .015"	+ .001 / - .000"	
60-2PG-09M	60	H	1.504	1.484	1.148	.868	.493	.493	.375	.188	8-32**	1/4
62-2PG-09M	62	H	1.554	1.534	1.148						8-32**	1/4
68-2PG-09M	68	H	1.704	1.684	1.185						8-32**	1/4
72-2PG-09M	72	H	1.805	1.785	1.185						8-32**	5/16
74-2PG-09M	74	H	1.855	1.835	1.215						8-32**	5/16
80-2PG-09M	80	H	2.005	1.985	1.500						8-32**	5/16
90-2PG-09M	90	H	2.256	2.236							8-32**	5/16
100-2PG-09M	100	H	2.506	2.486							8-32**	5/16
120-2PG-09M	120	H	3.008	2.988							10-32**	3/8



Type H

P/N Construction: (Code Number) (Bore Diameter) (Type)(Material Code)

PULLEY DIAMETER TOLERANCES	NOTES
60 - 80 Teeth = +.003 / -.000	* One (1) setscrew furnished.
81 - 120 Teeth = +.004 / -.000	** Two (2) setscrews furnished at 90 degrees.
2PG Working Depth = .0295"	

Ph: (217) 428-9043  
 Fx: (877) I FAX DSI



Email: info@DSIpulleys.com  
 Website: www.DSIpulleys.com