


3MM HTD® Pitch Timing Belt Pulleys

For 9MM Belts Type H

Clear Anodized Aluminum Alloy

ALL DIMENSIONS IN INCHES

Code Number	# of Teeth	Type	Pulley Pitch Diam	Pulley Diam	Hub Diam +/- .015"	Overall Width +/- .010"	Face Width +/- .010"	Belt Width +/- .010"	Hub Width +/- .015"	Setscrew Location +/- .015"	Setscrew Size	Stock Bore Diam +.001/- .000"
18-3HTD-09M	18	H	.677	.647	.442	.812	.506	.506	.306	.153	8-32**	1/4
19-3HTD-09M	19	H	.714	.684	.468						8-32**	1/4
20-3HTD-09M	20	H	.752	.722	.500						8-32**	1/4
22-3HTD-09M	22	H	.827	.797	.562						8-32**	1/4
24-3HTD-09M	24	H	.902	.872	.625						8-32**	1/4
25-3HTD-09M	25	H	.940	.910	.625						8-32**	1/4
26-3HTD-09M	26	H	.977	.947	.625						8-32**	1/4
28-3HTD-09M	28	H	1.053	1.023	.701						8-32**	1/4
30-3HTD-09M	30	H	1.128	1.098	.776						8-32**	1/4
32-3HTD-09M	32	H	1.203	1.173	.851						8-32**	1/4
34-3HTD-09M	34	H	1.278	1.248	.921	.834	.527	.527	.307	.153	8-32**	1/4
36-3HTD-09M	36	H	1.353	1.323	1.000						8-32**	1/4
38-3HTD-09M	38	H	1.429	1.399	1.075						8-32**	1/4
40-3HTD-09M	40	H	1.504	1.474	1.150						8-32**	1/4
44-3HTD-09M	44	H	1.654	1.624	1.300						8-32**	1/4
48-3HTD-09M	48	H	1.805	1.775	1.250	.875	.500	.500	.375	.188	8-32**	5/16
50-3HTD-09M	50	H	1.880	1.850							8-32**	5/16
56-3HTD-09M	56	H	2.105	2.075							8-32**	5/16
60-3HTD-09M	60	H	2.256	2.226							8-32**	5/16
62-3HTD-09M	62	H	2.331	2.301							8-32**	5/16
72-3HTD-09M	72	H	2.707	2.677							8-32**	5/16



Type H

P/N Construction: (Code Number) (Bore Diameter) (Type)(Material Code)

PULLEY DIAMETER TOLERANCES	NOTES
18 - 27 Teeth = +.002 / -.000	* One (1) setscrew furnished.
28 - 52 Teeth = +.003 / -.000	** Two (2) setscrews furnished at 90 degrees.
53 - 72 Teeth = +.004 / -.000	
3HTD Working Depth = .048"	

Ph: (217) 428-9043
Fx: (877) 1 FAX DSI



Email: info@DSIpulleys.com
Website: www.DSIpulleys.com