


# 3MM PowerGrip® Pitch Timing Belt Pulleys

## For 9MM Belts    Type H

Clear Anodized Aluminum Alloy

ALL DIMENSIONS IN INCHES														
	Code Number	# of Teeth	Type	Pulley Pitch Diam	Pulley Diam		Hub Diam	Overall Width	Face Width	Belt Width	Hub Width	Setscrew Location	Setscrew Size	Stock Bore Diam
							$\pm .015"$	$\pm .010"$	$\pm .010"$	$\pm .010"$	$\pm .015"$	$\pm .015"$	$\pm .015"$	$\pm .001 / -.000"$
 <p style="text-align: center;">Type H</p>	48-3PG-09M	48	H	1.805	1.775		1.250	.875	.500	.500	.375	.188	8-32**	5/16
	50-3PG-09M	50	H	1.880	1.850								8-32**	5/16
	56-3PG-09M	56	H	2.105	2.075								8-32**	5/16
	60-3PG-09M	60	H	2.256	2.226								8-32**	5/16
	62-3PG-09M	62	H	2.331	2.301								8-32**	5/16
	68-3PG-09M	68	H	2.557	2.527								8-32**	5/16
	72-3PG-09M	72	H	2.707	2.677								8-32**	5/16
	74-3PG-09M	74	H	2.782	2.752								8-32**	5/16
	80-3PG-09M	80	H	3.008	2.978								8-32**	5/16

P/N Construction: (Code Number) (Bore Diameter) (Type)(Material Code)

<p style="text-align: center;"><b>PULLEY DIAMETER TOLERANCES</b></p> <p>48 - 55 Teeth = <math>\pm .003 / -.000</math>          56 - 80 Teeth = <math>\pm .004 / -.000</math></p> <p>3PG Working Depth = <math>.045"</math></p>	<p style="text-align: center;"><b>NOTES</b></p> <p>* One (1) setscrew furnished.          ** Two (2) setscrews furnished at 90 degrees.</p>
--	---

Ph: (217) 428-9043  
 Fx: (877) I FAX DSI



Email: [info@DSIpulleys.com](mailto:info@DSIpulleys.com)  
 Website: [www.DSIpulleys.com](http://www.DSIpulleys.com)