


3MM PowerGrip® Pitch Timing Belt Pulleys

For 15MM Belts Type H

Clear Anodized Aluminum Alloy

ALL DIMENSIONS IN INCHES

Code Number	# of Teeth	Type	Pulley Pitch Diam	Pulley Diam	Hub Diam	Overall Width	Face Width	Belt Width	Hub Width	Setscrew Location	Setscrew Size	Stock Bore Diam
					+/- .015"	+/- .010"	+/- .010"	+/- .010"	+/- .015"	+/- .015"	+ .001 / - .000"	
48-3PG-09M	48	H	1.805	1.775	1.250	1.111	.736	.736	.375	.188	8-32**	5/16
50-3PG-09M	50	H	1.880	1.850							8-32**	5/16
56-3PG-09M	56	H	2.105	2.075							8-32**	5/16
60-3PG-09M	60	H	2.256	2.226							8-32**	5/16
62-3PG-09M	62	H	2.331	2.301							8-32**	5/16
68-3PG-09M	68	H	2.557	2.527							8-32**	5/16
72-3PG-09M	72	H	2.707	2.677							8-32**	5/16
74-3PG-09M	74	H	2.782	2.752							8-32**	5/16
80-3PG-09M	80	H	3.008	2.978							8-32**	5/16



Type H

P/N Construction: (Code Number) (Bore Diameter) (Type)(Material Code)

PULLEY DIAMETER TOLERANCES	NOTES
48 - 55 Teeth = +.003 / -.000	* One (1) setscrew furnished.
56 - 80 Teeth = +.004 / -.000	** Two (2) setscrews furnished at 90 degrees.
3PG Working Depth = .045"	

Ph: (217) 428-9043
 Fx: (877) I FAX DSI



Email: info@DSIpulleys.com
 Website: www.DSIpulleys.com