


5MM PowerGrip GT2® Pitch Timing Belt Pulleys

For 15MM Belts Type H & HW


Clear Anodized Aluminum Alloy

ALL DIMENSIONS IN INCHES



Code Number	# of Teeth	Type	Pulley Pitch Diam	Pulley Diam	Hub Diam +/- .015"	Overall Width +/- .010"	Face Width +/- .010"	Belt Width +/- .010"	Hub Width +/- .015"	Setscrew Location +/- .015"	Setscrew Size	Stock Bore Diam +.001/- .000"
12-5PG-15M	12	H	.752	.707	.437	1.031	.780	.780	.251	.125	M3**	1/4
13-5PG-15M	13	H	.815	.770	.500						M3**	1/4
14-5PG-15M	14	H	.877	.832	.500						M3**	1/4
15-5PG-15M	15	H	.940	.895	.562						M3**	1/4
16-5PG-15M	16	H	1.003	.958	.562						M3**	1/4
17-5PG-15M	17	H	1.065	1.020	.625						M3**	1/4
18-5PG-15M	18	H	1.128	1.083	.687						M3**	1/4
19-5PG-15M	19	H	1.191	1.146	.750						M3**	1/4
20-5PG-15M	20	H	1.253	1.208	.812						M3**	1/4
22-5PG-15M	22	H	1.379	1.334	.937						M3**	1/4
24-5PG-15M	24	H	1.504	1.459	1.000	1.157			.377	.188	M5**	3/8
25-5PG-15M	25	H	1.566	1.521	1.000						M5**	3/8
26-5PG-15M	26	H	1.629	1.584	1.062						M5**	3/8
28-5PG-15M	28	H	1.754	1.709	1.187	1.280			.500	.250	M6**	1/2
30-5PG-15M	30	H	1.880	1.835	1.187						M6**	1/2
32-5PG-15M	32	H	2.005	1.960	1.250						M6**	1/2
34-5PG-15M	34	H	2.130	2.085	1.375						M6**	1/2
36-5PG-15M	36	H	2.256	2.211	1.500						M6**	1/2
38-5PG-15M	38	H	2.381	2.336	1.500						M6**	1/2
40-5PG-15M	40	H	2.506	2.416	1.500						M6**	1/2

ALL DIMENSIONS IN INCHES



Code Number	# of Teeth	Type	Pulley Pitch Diam	Pulley Diam	Flange Diam +/- .020"	Hub Diam +/- .015"	Overall Width +/- .010"	Face Width +/- .010"	Belt Width +/- .010"	Hub Width +/- .015"	Setscrew Location +/- .015"	Setscrew Size	Stock Bore Diam +.001/- .000"
44-5PG-15M	44	HW	2.757	2.712		1.500	1.280	.780	.780	.500	.250	M6**	1/2
48-5PG-15M	48	HW	3.008	2.963		1.500						M6**	1/2
50-5PG-15M	50	HW	3.133	3.088		1.500						M6**	1/2
56-5PG-15M	56	HW	3.509	3.464		1.500						M6**	1/2
60-5PG-15M	60	HW	3.760	3.715		1.500						M6**	1/2
62-5PG-15M	62	HW	3.885	3.840		1.500						M6**	1/2
70-5PG-15M	70	HW	4.386	4.341		1.500						M6**	1/2
72-5PG-15M	72	HW	4.511	4.466		1.500						M6**	1/2

P/N Construction: (Code Number) (Bore Diameter) (Type)(Material Code)

PULLEY DIAMETER TOLERANCES	NOTES
10 - 16 Teeth = +.002 / -.000	* One (1) setscrew furnished.
17 - 32 Teeth = +.003 / -.000	** Two (2) setscrews furnished at 90 degrees.
33 - 64 Teeth = +.004 / -.000	
65 - 72 Teeth = +.005 / -.000	
5PG Working Depth = .076"	

Ph: (217) 428-9043
Fx: (877) 1 FAX DSI



Email: info@DSIpulleys.com
Website: www.DSIpulleys.com