


# L (.375") Pitch Timing Belt Pulleys For 1/2" Belts Type HF

Clear Anodized Aluminum Alloy

## ALL DIMENSIONS IN INCHES

Code Number	# of Teeth	Type	Pulley Pitch Diam	Pulley Diam	Flange Diam +/- .020"	Hub Diam +/- .015"	Overall Width +/- .010"	Face Width +/- .010"	Belt Width +/- .005"	Hub Width +/- .015"	Setscrew Location +/- .015"	Setscrew Size	Stock Bore Diam +/- .001/- .000"
10-L-050	10	HF	1.194	1.164	1.438	.813	1.125	.750	.610	.375	.188	1/4-20**	3/8, 1/2***
11-L-050	11	HF	1.313	1.283	1.531	.938	1.125			.375	.188	1/4-20**	3/8, 1/2***
12-L-050	12	HF	1.432	1.402	1.656	1.063	1.250			.500	.250	1/4-20**	3/8, 1/2***
13-L-050	13	HF	1.552	1.522	1.781	1.094						1/4-20**	3/8, 1/2***
14-L-050	14	HF	1.671	1.641	1.906	1.125						1/4-20**	3/8, 1/2***
15-L-050	15	HF	1.790	1.760	2.031	1.250						1/4-20**	3/8, 1/2***
16-L-050	16	HF	1.910	1.880	2.125	1.438	1.375			.625	.312	1/4-20**	1/2, 5/8
17-L-050	17	HF	2.029	1.999	2.250	1.500						1/4-20**	1/2, 5/8
18-L-050	18	HF	2.149	2.119	2.375	1.563						1/4-20**	1/2, 5/8
19-L-050	19	HF	2.268	2.238	2.500	1.625						1/4-20**	1/2, 5/8
20-L-050	20	HF	2.387	2.357	2.625	1.688						1/4-20**	1/2, 5/8
21-L-050	21	HF	2.507	2.477	2.750	1.875	1.438			.688	.344	1/4-20**	1/2, 5/8
22-L-050	22	HF	2.626	2.596	2.875	2.000	1.500			.750	.375	1/4-20**	1/2, 5/8
24-L-050	24	HF	2.865	2.835	3.094	2.250	1.500			.750	.375	1/4-20**	1/2, 5/8



Type HF

P/N Construction: (Code Number) (Bore Diameter) (Type)(Material Code)

PULLEY DIAMETER TOLERANCES	NOTES
10 - 17 Teeth = +.003 / -.000	** Two (2) setscrews furnished at 90 degrees.
18 - 24 Teeth = +.004 / -.000	*** - Pulley with 3/8" bore uses two (2) 10-32 UNC setscrews.
XL Working Depth = .056"	

Ph: (217) 428-9043  
Fx: (877) I FAX DSI



Email: info@DSIpulleys.com  
Website: www.DSIpulleys.com