


XL (.200") Pitch Timing Belt Pulleys

For 3/8" Belts Type H

Clear Anodized Aluminum Alloy

ALL DIMENSIONS IN INCHES

| Code Number | # of Teeth | Type | Pulley Pitch Diam | Pulley Diam | Flange Diam +/- .020" | Hub Diam +/- .015" | Overall Width +/- .010" | Face Width +/- .010" | Belt Width +/- .010" | Hub Width +/- .015" | Setscrew Location +/- .015" | Setscrew Size | Stock Bore Diam + .001 / - .000" |
|-------------|------------|------|-------------------|-------------|--------------------------|-----------------------|----------------------------|-------------------------|-------------------------|------------------------|--------------------------------|---------------|-------------------------------------|
| 10-XL-037 | 10 | H | .637 | .617 | | .438 | .813 | .563 | .563 | .250 | .125 | 8-32* | 3/16, 1/4*** |
| 11-XL-037 | 11 | H | .700 | .680 | | .500 | | | | | | 8-32* | 3/16, 1/4*** |
| 12-XL-037 | 12 | H | .764 | .744 | | .563 | | | | | | 6-40** | 3/16 |
| 14-XL-037 | 14 | H | .891 | .871 | | .625 | | | | | | 8-32** | 1/4, 5/16 |
| 15-XL-037 | 15 | H | .955 | .935 | | .688 | .875 | | | .312 | .156 | 8-32** | 1/4, 5/16, 3/8 |
| 16-XL-037 | 16 | H | 1.019 | .999 | | .750 | | | | | | 8-32** | 1/4, 5/16 |
| 17-XL-037 | 17 | H | 1.082 | 1.062 | | .813 | | | | | | 8-32** | 1/4 |
| 18-XL-037 | 18 | H | 1.146 | 1.126 | | .875 | | | | | | 8-32** | 1/4, 5/16, 3/8 |
| 19-XL-037 | 19 | H | 1.210 | 1.190 | | .875 | | | | | | 8-32** | 1/4 |
| 20-XL-037 | 20 | H | 1.273 | 1.253 | | .938 | .938 | | | .375 | .188 | 10-32** | 1/4, 5/16, 3/8*** |
| 21-XL-037 | 21 | H | 1.337 | 1.317 | | 1.000 | | | | | | 8-32** | 1/4 |
| 22-XL-037 | 22 | H | 1.401 | 1.381 | | 1.063 | | | | | | 10-32** | 1/4, 5/16, 3/8*** |
| 23-XL-037 | 23 | H | 1.464 | 1.444 | | 1.125 | | | | | | 10-32** | 1/4, 3/8*** |
| 24-XL-037 | 24 | H | 1.528 | 1.508 | | 1.188 | | | | | | 10-32** | 1/4, 5/16, 3/8*** |
| 25-XL-037 | 25 | H | 1.592 | 1.572 | | 1.250 | | | | | | 10-32** | 1/4, 5/16, 3/8*** |
| 27-XL-037 | 27 | H | 1.719 | 1.699 | | 1.250 | | | | | | 8-32** | 5/16 |
| 28-XL-037 | 28 | H | 1.783 | 1.763 | | 1.250 | | | | | | 10-32** | 1/4, 5/16, 3/8*** |
| 29-XL-037 | 29 | H | 1.846 | 1.826 | | 1.313 | | | | | | 8-32** | 5/16 |
| 30-XL-037 | 30 | H | 1.910 | 1.890 | | 1.375 | | | | | | 10-32** | 1/4, 5/16, 3/8*** |
| 32-XL-037 | 32 | H | 2.037 | 2.017 | | 1.500 | 1.000 | | | .437 | .219 | 1/4-20** | 5/16, 3/8, 1/2*** |
| 36-XL-037 | 36 | H | 2.292 | 2.272 | | 1.500 | 1.000 | | | .437 | .219 | 1/4-20** | 5/16, 3/8, 1/2*** |



Type H

P/N Construction: (Code Number) (Bore Diameter) (Type)(Material Code)

| PULLEY DIAMETER TOLERANCES | NOTES |
|-------------------------------|--|
| 10 - 16 Teeth = +.002 / -.000 | * One (1) setscrew furnished. |
| 17 - 31 Teeth = +.003 / -.000 | ** Two (2) setscrews furnished at 90 degrees. |
| 32 - 36 Teeth = +.004 / -.000 | *** - Pulley with 3/16" bore uses one (1) 6-40 UNF setscrew. |
| | - Pulley with 1/4" AND 5/16" bore uses two (2) 8-32 UNC setscrews. |
| | - Pulley with 3/8" bore uses two (2) 10-32 UNC setscrews. |
| XL Working Depth = .056" | |

Ph: (217) 428-9043
 Fx: (877) 1 FAX DSI



Email: info@DSIpulleys.com
 Website: www.DSIpulleys.com